HOOLASUSPENSION

TYPE:

PROJECT NAME:



With its very light and minimal design hoola creates an archetypical light circle. The soft light is directed upwards and downwards while its highly efficient led-light curves along with the lamp shape. Hoola is available in 60, 100 and 140cm diameter. Hoola will be a real eyecatcher when different diameters are combined. It can be arranged in horizontal, angled or even vertical positions. The lamps can be place close to a ceiling, in free open spaces or vertically along the wall.

hoola 60 dim



lamp type	LED
colour temp.	2400K / 2700K / 3000K
max. watt	36W
voltage	120V
lumen	2120
class	1
gear	incorporated (dimmable)
diameter	600 mm (23.62")
height	25 (max 2500) mm (0.98"

white T92H3DWLD black T92H3DZLD order code 2700K

white T92H9DWLD


black T92H9DZLD

white T92H1DWLD

black T92H1DZLD

order code 3000K

60 dim hoola 100 dim




lamp type	LED
colour temp.	2400K / 2700K / 3000K
max. watt	60W
voltage	120V
lumen	3540
class	1
gear	incorporated (dimmable)
diameter	1000 mm (39.37")
height	25 (max 2500) mm (0.98")

order code 2400K white T92H4DWLD black T92H4DZLD order code 2700K

white T92H10DWLD
black T92H10DZLD

order code 3000K white T92H2DWLD black T92H2DZLD

hoola 140 dim



e LED	lamp type
o. 2400K / 2700K / 3000K	colour temp.
tt 90W	max. watt
e 120V	voltage
n 4950	lumen
s 1	class
ar incorporated (dimmable)	gear
er 1400 mm (55.11")	diameter
nt 25 (max 2500) mm (0.98"	height

order code 2400K			
white	T92H17DWLD		
black	T92H17DZLD		
	7001		

order code 2700K		
wh	nite	T92H14DWLD
bla	ick .	T92H14DZLD

order code 3000K white T92H13DWLD black T92H13DZLD

ORDERING INFO				
Mode	el (Order Code)	Finish	LED	Voltage/Dimming
		WhiteBlack	○ 2400K○ 2700K	120V Phase Dimming (Integral Driver) 120V 0-10V Dimming (Remote Driver)
la laterate			○ 3000K	277V 0-10V Dimming (Remote Driver)

tossB

SPECIFICATION SHEET